

Screws

► Direct fixing screws

Shallow countersunk head



- Shallow countersunk head
- Pozidrive screw
- Galvanised steel

Dimensions mm	Order no.	PU
ø 4.5 x 13.5	0 073 751	200 ea.
ø 6.3 x 10.5	0 051 264	200 ea.
ø 6.3 x 11	0 047 451	200 ea.
ø 6.3 x 12.5	0 073 752	200 ea.
ø 6.3 x 14	0 051 265	200 ea.
ø 6.3 x 15	0 073 889	200 ea.
ø 6.3 x 18	0 052 799	200 ea.

Deep countersunk head



- Deep countersunk head
- Pozidrive screw
- Galvanised steel

Dimensions mm	Order no.	PU
ø 6.3 x 10.5	0 073 890	200 ea.
ø 6.3 x 14	0 047 452	200 ea.

Panhead



- Panhead
- Pozidrive screw
- Steel, nickel-plated

Dimensions mm	Order no.	PU
ø 6.3 x 11	0 040 006	200 ea.
ø 6.3 x 13	0 040 007	200 ea.
ø 6.3 x 15	0 040 008	200 ea.

Countersunk screw



- Countersunk screw
- M5 x 11 mm
- Pozidrive screw
- Steel, nickel-plated

Order no.	PU
0 045 164	200 ea.