


- 2 - 15 Light concepts
- 17 - 87 LED lights
- 88 - 131 Fluorescent lights
- 132 - 159 Low-voltage halogen lights
- 160 - 167 Switch systems
- 168 - 170 Accessories

LED GlasLine



Light type: Surface-mounted LED
 Function: Ambient light
 Specific characteristics: Surface-mounting LED light for illuminating the edge of an 8 mm thick glass shelf to great effect
 Profile length 600 mm, can be shortened by any length at one end
 It is recommended to use a white glass shelf (Optiwhite) with matt-finished edge.
 Finish: Aluminium silver anodised
 Ordering information: LED ballast and mains-voltage feeder need to be ordered separately, see below or refer to pages 72 - 74

Light tone	Order no.	PU
cool white	9 069 826	1
warm white	9 070 031	1
blue	9 070 237	1


Accessories

Article	Order no.	PU
LED ballast 6 / 12 / 24 V, 20 W	9 084 283	1
Mains-voltage feeder with Euro connector 1500 mm	9 084 627	1
LED extension lead 1800 mm	0 041 762	1
3-way LED distributor 180 mm	0 043 874	1

For further LED ballasts and accessories, see pages 72 - 79

Technical details in brief

Operating voltage: 6 Volt DC
 Output: 1,2 Watt
 Number of LEDs: 7
 IP rating: IP 20
 Light tone: cool white / warm white / blue
 Test marks and symbols:
 Supply lead: 1700 mm
 Dimmable: no
 Plug connection: LED mini plug connection
 Connection to: LED ballast



Assembly

