

- ▶ Quadro V6 drawer runner with Silent System, bulk packaging
- ▶ Full extension runner, load capacity 30 kg

## Drawer runner



- ▶ With integrated Silent System
- ▶ Load capacity to EN 15338 Level 3
- ▶ Slide on installation
- ▶ Steel, galvanised

### Installed width 12.5 mm

Nominal length mm	Order no.		PU
	left	right	
260	9 047 180	9 047 181	20 ea.
300	9 039 093	9 039 095	20 ea.
350	9 046 304	9 046 305	20 ea.
420	9 046 294	9 046 295	20 ea.
470	9 046 288	9 046 289	20 ea.
520	9 047 171	9 047 172	20 ea.

### Installed width 10.5 mm

Nominal length mm	Order no.		PU
	left	right	
260	9 047 392	9 047 393	20 ea.
300	9 065 870	9 065 871	20 ea.
350	9 047 443	9 047 444	20 ea.
420	9 047 450	9 047 451	20 ea.
470	9 047 452	9 047 453	20 ea.
520	9 047 454	9 047 455	20 ea.

### Installed width 9.5 mm

Nominal length mm	Order no.		PU
	left	right	
260	9 047 281	9 047 282	20 ea.
300	9 065 911	9 065 912	20 ea.
350	9 047 284	9 047 285	20 ea.
420	9 047 287	9 047 288	20 ea.
470	9 047 289	9 047 290	20 ea.
520	9 047 293	9 047 294	20 ea.

## Quadro installed width

With various Quadro installed widths (EB) to choose from, it is possible to work with different carcass side panel thicknesses (KD) – without having to change the drawer dimensions. The following dimensions apply:

KD mm	16	18	19
EB mm	12.5	10.5	9.5
A mm	23	21	20

