

Fast assembly concealed hinge

- ▶ Intermat 9930 with cup in Sensys design for corner cabinet folding doors
- ▶ Opening angle 50° / 65°



- ▶ Concealed hinge with clip on installation
- ▶ Quality classification under EN 15570, Level 2
- ▶ Cup diameter 35 mm
- ▶ Cup depth 12.8 mm
- ▶ Diagonal adjustment + 9.5 mm / - 9.5 mm
- ▶ Integrated overlay adjustment, see diagram
- ▶ For integrated height adjustment, see diagram
- ▶ Height adjustment at mounting plate
- ▶ Hinge arm material: zinc die-cast nickel plated
- ▶ Hinge cup material: steel, nickel plated

Intermat 9930, opening angle 50° / 65°

overlay	
Base B 24 mm	PU

Cup assembly	Drilling pattern	Mounting drilling ø x T mm		
For screwing on TH 52		-	9 090 109	1/50 ea.
For pressing in TH 53		ø 10 x 11	9 090 110	1/50 ea.
Flash fast assembly TH 54			9 090 111	1/50 ea.
Fix fast assembly THS 55		ø 10 x 6	9 090 113	1/50 ea.
For screwing on TB 52		-	9 090 115	1/50 ea.
For pressing in TB 53		ø 8 x 11	9 090 116	1/50 ea.
Flash fast assembly TB 54			9 090 117	1/50 ea.
Fix fast assembly TB 55		ø 8 x 6	9 090 119	1/50 ea.